



BCC01

BCC02

AVAILABLE AS

1914U3-7 BCC01 with charger DC4002 | 1914U0-3 BCC02 with charger DC4002

USER BENEFITS

- Ideal for sites where numerous batteries are frequently used, ensuring multiple batteries are always ready for use
- **BCC01:** Equipped with 8 charging ports for XGT and LXT batteries. LXT batteries can be charged using interchangeable ADP10 adapters.
- **BCC02:** Features 12 charging ports for XGT batteries.
- Designed to connect to MAKPAC carriers for easier transportation and matches the size of the MAKPAC type 4 carrying case.
- With low power consumption, multiple units can be connected to a single 16 A power outlet, making it efficient for nighttime charging.
- Battery charging case (BCC01/BCC02) can also charge batteries using PDC (Portable Power Connector) with BAC01 (Voltage Inverter), enabling charging without a power outlet.
- IPX4 rating; protects against dust and water

TECHNICAL SPECIFICATIONS


	BCC01	BCC02
Chargable battery voltage	XGT 40 V max / LXT 18 / 14,4 V*1	XGT 40 V max
Number of charging ports	8	12
Charging current	1,6 A (XGT 40 V max) 2,1 A (LXT 18 / 14,4 V)*1	1,6 A
Chargable batteries	All XGT 40 V max all LXT 18 / 14,4 V*1*2	BL4020, BL4025, BL4040 BL4040F
Total charging time	560 min (8x BL4080F) 320 min (8x BL1860B)	435 min (12x BL4040F)
Dimensions (L×W×H)	295 x 407 x 320 mm	
Weight	7,5 kg*3	7,8 kg*3

*1 with ADP10 adapter | *2 BL1430A/AP cannot be charged | *3 with charger DC4002

PRODUCT HIGHLIGHTS



Versatile Case Placement
The case has a tool-free removable lid and can be placed vertically or horizontally on a shelf, making it easy to set up charging stations.



Efficient battery charging
The switch charging feature allows the device to charge four batteries simultaneously and automatically switches between them to ensure all batteries are charged efficiently.

CHARGING TIMES

Platform	Battery	BCC01			BCC02
		4 ports	8 ports	12 ports	
XGT	BL4020	75 min	150 min	255 min	
	BL4025	90 min	180 min	270 min	
	BL4040	145 min	290 min	435 min	
	BL4040F	145 min	290 min	435 min	
	BL4050F	175 min	350 min	-	
	BL4080F	280 min	560 min	-	
LXT*	BL1815N	40 min	80 min	-	
	BL1820B	55 min	110 min	-	
	BL1830B	80 min	160 min	-	
	BL1840B	110 min	220 min	-	
	BL1850B	135 min	270 min	-	
	BL1860B	160 min	320 min	-	

* with ADP10 adapter

ACCESSORIES



RELATED PRODUCTS



XGT 40 V max
191N09-8
DC40RB - Two port fast charger



XGT 40 V max
1911L9-4
DC40WA - Two port charger



XGT 40 V max
191E07-8
DC40RA - Fast charger



XGT 40 V max
191M90-3
DC40RC - charger



AVAILABLE AS

B0007CGZ without battery and charger

PRODUCT HIGHLIGHTS



Effortless connectivity
Battery adapter connects seamlessly into the tool, facilitated by a large lever for easy one-hand attachment and detachment.



Speed control dial
Enables the selection of rotation speed to suit various applications

1. 6.000 min⁻¹
2. 6.500 min⁻¹
3. 9.000 min⁻¹
4. 11.500 min⁻¹
5. 12.000 min⁻¹



Dust Collection Options
This tool offers flexible dust collection options, allowing users to choose between self dust collection with an attached dust bag or enhanced dust control by connecting to a vacuum cleaner.



Optimal Control and Maneuverability
Designed for precision, the tool's handle is positioned close to the sanding surface and has an optimally balanced center of gravity, ensuring excellent maneuverability for fine operations.

NOISE AND VIBRATION

Sound pressure level: **77 dB(A)**
Vibration level (sanding metal plate): **3,1 m/s²**

COMPATIBILITY

Recommended: **BL4020, BL4025, BL4040, BL4040F, PDC01, PDC1200, PDC1500**
Compatible: **BL4050F, BL4080F**

RELATED PRODUCTS



XGT 40 V max
B0004CG
Battery powered random orbit sander



XGT 40 V max
B0006CG
Battery powered orbital sander



LXT 18 V
DB0381
Cordless finishing sander

USER BENEFITS

- Suitable for carpenter, craftsmen and contractors.
- Excellent maneuverability is achieved through a connector-style battery connection that reduces hand load and keeps the overall height low.
- Lightweight and low height design makes it similar to pneumatic sanders, ensuring ease of use and portability.
- Optimal handle design places the handle close to the sanding surface with a balanced center of gravity for precise control during fine operations.
- High efficiency and power are provided by the 40 V max XGT Li-Ion battery with a BL motor, ensuring stable sanding with consistent speed control.
- Low maintenance and longevity are achieved by eliminating the need for air compressors, periodic lubrication or maintenance of air piping, reducing downtime and increasing productivity compared to pneumatic sanders.
- The tool also features soft start, variable speed control, constant speed control, an electric brake, and an anti-restart function.

TECHNICAL SPECIFICATIONS

Accumulator voltage	40 V max - XGT
Orbits per minute	6.000 - 12.000 min ⁻¹
Orbit diameter	ø 2,0 mm
Pad size	93x185 mm
Abrasive paper size	93x185 / 93x228 mm
Power supply cord	1,6 m
Dimensions (L×W×H)*	263 x 92 x 106 mm
Weight*	1,1 kg

* without power supply cord and battery adapter

ACCESSORIES

Battery adapter - 1,6 m
1914H3-6



Battery adapter - 5 m
1914H5-2



Protection cover
1914H7-8



Harness
1914H8-6



Rectangular pad
1915E5-7



Punch plate
451271-6



Dust bag
122G32-0



Arm band
194679-8



AWS wireless connector WUT01
198900-7



Dust nozzle
413Y47-9



MAKITA d.o.o.,
Brnčičeva 17, 1231 Ljubljana-Črnuče, Slovenia
T: +386 (0) 59 083 600, E: info@makita.si



AVAILABLE AS

DTC104ZK without battery and charger, with metal case

PRODUCT HIGHLIGHTS

**Automatic reverse function**

The blades automatically return to their original position after completing the cutting operation, enhancing work efficiency.

**270° rotatable cutting head**

The head rotates 270 degrees, making it easy to use in a variety of orientations.

**Optional shoulder belt**

2 tethering points for optional attachment of shoulder belt.

Cutting capacity	
Polyethylene power cable:	ø72 mm / 4 x 325 mm ²
PVC insulated multi-core cable:	ø77 mm / 3 x 325 mm ²
Annealed copper wire:	ø105 mm / 1,300 mm ²
Hard-drawn copper wire:	ø90 mm / 1,300 mm ²
Aluminum wire:	ø105 mm / 1,300mm ²

USER BENEFITS

- Capable of cutting large-diameter electric wires
- LED job light with afterglow function
- 2 tethering holes for attaching a shoulder strap
- 270° rotatable head for working in variety of positions
- Trigger-lock function to minimize accidental tool activation during transport and handling

TECHNICAL SPECIFICATIONS

Accumulator voltage	18 V LXT
Cutting capacity Ø	Al, Annealed copper wire: 105 mm / 1.300 mm ²
Cutting capacity Ø	Hard-drawn copper wire: 90 mm / 1.300 mm ²
Maximum blade opening width	105 mm
Output force	120 kN
Dimensions (L×W×H)* ¹	718 x 123 x 267 mm
Weight* ¹	10,5 kg

*¹ With BL1860B battery

ACCESSORIES

Shoulder belt
161347-8



COMPATIBILITY

Recommended: **BL1815N, BL1820B, BL1830B, BL1840B, BL1850B, BL1860B**

RELATED PRODUCTS



LXT 18 V
DTC102
Cordless cable
cutter



LXT 18 V
DTC103
Cordless cable
cutter



LXT 18 V
DTC301
Cordless
crimper



LXT 18 V
DTC302
Cordless
crimper



USER BENEFITS

- Capable of crimping terminals onto large-diameter electric wires
- Single LED job light with afterglow function
- Trigger-lock function to minimize accidental pulling of the switch trigger
- Auto retract function with on/off option enables the ram to automatically return to original position
- 270° rotatable head for working in variety of positions
- Die release pin and knob for easy die replacement
- 2 tethering straps for attaching a shoulder belt

TECHNICAL SPECIFICATIONS

	DTC301	DTC302
Accumulator voltage	18 V LXT	18 V LXT
Output force	120 kN	
Ram stroke length	31 mm	42 mm
Capacity Ø: Cu	19,5 mm	22,5 mm
Capacity Ø: Al	19,5 mm	19,5 mm
Dimensions (L×W×H)	415 x 92 x 346 mm	437 x 94 x 349 mm
Weight* ¹	7,1 kg	7,8 kg

*¹ with BL1860B battery

AVAILABLE AS

DTC301ZK without battery and charger, with plastic case | DTC302ZK without battery and charger, with plastic case

PRODUCT HIGHLIGHTS



270° crimping head
The head rotates 270 degrees, making it easy to use in a variety of orientations.



Auto retract function
The ram automatically retracts to its original position after completing the crimping operation, enhancing work efficiency.



LED light
With afterglow function.



Manual ram release
When the auto retract function is off you can retract the ram manually by pressing the release knob.

ACCESSORIES

Hex die	Range (mm ²)	A (mm)	B (mm)	C (mm)	Code
K18	Cu 95 Al 70	18	7,0	14	ZM00000222
K20	Cu 120 Al 95	19,8	7,6	14	ZM00000223
K22	Cu 150 Al 120	22,3	9,6	12	ZM00000224



Shoulder belt
161347-8

COMPATIBILITY

Recommended: BL1815N, BL1820B, BL1830B, BL1840B, BL1850B, BL1860B

RELATED PRODUCTS



LXT 18 V
DTC102
Cordless cable
cutter



LXT 18 V
DTC103
Cordless cable
cutter



AVAILABLE AS

DUV320Z without battery and charger

USER BENEFITS

- Encourages healthy lawn growth with aeration and dethatching by improving aeration, enhancing water penetration and promoting growth
- Compact, lightweight, and highly maneuverable, ideal for home lawn care
- Foldable design for easy storage
- Two types of blades for different applications; scarifying and dethatching
- Simple adjustment of the scarifying depth using the central height adjustment lever
- IPX4 water resistance allows for easy cleaning of the cutting deck
- Warning lamp at the back of the battery cover indicates low battery capacity or battery error
- For maintenance of lawns up to 128 m²

TECHNICAL SPECIFICATIONS

Accumulator voltage	18 V LXT
No load speed	3.300 min ⁻¹
Working width	320 mm
Grass catcher capacity	30 l
Working high - 4 positions	-8-+4 mm
Dimensions (L×W×H)	1.035 x 565 x 995 mm
Weight*1	10,4 kg

*1 With BL1860B battery


PRODUCT HIGHLIGHTS




Foldable handle - 3 stages
The handle can be folded in half with two levers and in three stages with the levers and thumb screws.



Easy cleaning
The scarifier features IPX4 water protection for easy cleaning of the cutting deck with a water hose.



Scarifying blade
Cuts through old roots to promote healthy growth and through lawn and soil to improve water and air penetration.



Dethatching blade
For removing deposited lawn clippings, accumulated moss, etc.

ACCESSORIES

Scarifying blade
YA00001316

Dethatching blade
YA00001317



NOISE AND VIBRATION

Sound pressure level: **75 dB(A)**, Sound power level: **89 dB(A)**,
Vibration level: **≤2,5 m/s²**

COMPATIBILITY

Recommended: **BL1850B, BL1860B**
Compatible: **BL1815N, BL1820B, BL1830B, BL1840B**

RELATED PRODUCTS



XGT 40 V max
UV001G
Cordless scarifier



LXT 18 V
DLM330
Cordless lawn
mower



LXT 18 +18 V
DLM382
Cordless lawn
mower



LXT 18 V
DUR193
Cordless grass
trimmer



MAKITA d.o.o.,
Brnčičeva 17, 1231 Ljubljana-Črnuče, Slovenia
T: +386 (0) 59 083 600, E: info@makita.si



USER BENEFITS

- Powerful 800 W motor delivers 3,0 J of impact energy to handle the most demanding applications.
- Three operation modes: Rotation only / Rotation with hammering / Hammering only
- Torque limiter engineered to minimize gear damage by automatically disengaging gears if the bit binds.
- Connectable to Makita vacuum cleaners.
- Recessed lock-on button for continuous use.

TECHNICAL SPECIFICATIONS

	HR2670	HR2670FT
Continuous rating input		800 W
Shank adapted for		SDS-PLUS
Chuck capacity	-	1,5-13 mm
No load speed		0-1,500 min ⁻¹
Blows per min		0-4,500 min ⁻¹
Impact energy		3,0 J
Capacity Ø: steel / wood / concrete		13 / 32 / 26 mm
Capacity Ø: core bit		68 mm
Capacity Ø: diamond core bit		80 mm
Dimensions (L×W×H)	362 x 77 x 207 mm	390 x 77 x 207 mm
Weight	3,4 kg	3,3 kg

AVAILABLE AS

HR2670 with normal chuck for SDS-PLUS | HR2670FT with two quick change chucks: for SDS-PLUS / cylindrical

PRODUCT HIGHLIGHTS



LED light - HR2670FT only
Illuminates the work area for easier drill centering.



Reverse rotation with no speed/torque loss
By turning the brush holder unit to switch to reverse, the speed and torque remain the same.



Dust extraction pad - optional
The suction power of the vacuum cleaner sticks the pad to the wall and collects dust during drilling.



Variable speed control by trigger

ACCESSORIES

Dust cup for drilling
HR2670 1914L7-6
HR2670FT 1914L8-4



Quick change chuck for SDS-PLUS
191F47-2



Hammer bit grease 100 ml
198993-4



Dust cup for chiseling
HR2670 1914L9-2
HR2670FT 1914M0-7



Quick change chuck 1,5-13 mm
191F46-4



Dust extraction pad
1914X3-8



Adapter SDS-PLUS > 1/2"-20 UNF
D-14093



NOISE AND VIBRATION HR2670

Sound pressure/power level: **94/102 dB(A)**, Vibration level (hammer drilling into concrete/chiseling): **16,1/14,2 m/s²**

NOISE AND VIBRATION HR2670FT

Sound pressure/power level: **94/102 dB(A)**, Vibration level (hammer drilling into concrete/chiseling): **15,7/14,0 m/s²**

RELATED PRODUCTS



MAKITA d.o.o.,
Brnčičeva 17, 1231 Ljubljana-Črnuče, Slovenia
T: +386 (0) 59 083 600, E: info@makita.si

www.makita.si



AVAILABLE AS

HS013GZ without battery and charger | HS013GT101 with BL4050F battery and DC40RA charger

USER BENEFITS

- Suitable for demanding tasks such as cutting large timber, framing and roofing, slicing through railway sleepers, heavy-duty carpentry, and construction site work, with the ability to cut materials up to 150mm thick in a single stroke.
- Lightweight design and enhanced maneuverability with compact tool body
- Equipped with a blade stabilizer for suppressing blade vibration
- 75 cuts with fully charged BL4050F battery
- Supplied support stand keeps the tool safe during storage and lets you easily access it without bending over
- The circular saw features electric brake, anti restart function, soft start, and dust collection

TECHNICAL SPECIFICATIONS

Accumulator voltage	40 V max XGT
No load speed	2.100 min ⁻¹
Blade/hole diameter	415/30 mm
Max cutting capacity at 0°	158 mm
Max cutting capacity 45°	106 mm
Bevel range	0-45°
Dimensions (L×W×H)	606 x 233 x 476 mm
Weight*	11,0 kg

* With BL4040 battery

PRODUCT HIGHLIGHTS



High-Capacity Cordless Circular Saw
The cordless circular saw features a 415 mm saw blade and offers a maximum cutting capacity of 158 mm, providing powerful, efficient cuts for a variety of tasks.



Compact Design
The tool's 65 mm narrower body, compared to the previous corded model, features a BL motor that improves stability and maneuverability during blade changes.



Blade stabilizer
Reduces vibration by locking the lever into the locked position.



Support stand
Supplied support stand keeps the tool safe during storage and lets you easily access it without bending over

ACCESSORIES

Efficut saw blade for wood
E-24848



AWS unit WUT01
198900-7



Support stand
4131E7-2



Guide rail
164019-4



NOISE AND VIBRATION

Sound pressure level: **98 dB(A)**,
Sound power level: **106 dB(A)**, Vibration level: **2,5 m/s²**

COMPATIBILITY

Recommended: **BL4080F, BL4050F, BL4040F**
Compatible: **BL4040**

RELATED PRODUCTS



40 V max XGT
HS011G
Cordless Circular Saw - 270 mm



40 V max XGT
RS002G
Cordless Rear Handle Saw - 260 mm



40 V max XGT
HS009G
Cordless Circular Saw - 235 mm


AVAILABLE AS

PS001GZ without battery and charger

PRODUCT HIGHLIGHTS

Cleaning edges, floor joints

The splash guard can be removed for better access when cleaning joints, grooves, wall edges.


Easy install/removal of accessories

Center the accessory to the head, press it lightly against the floor and use forward rotation for installing/ reverse rotation for removal.

Speed mode / no load speed	Application
 3. High / 600 min ⁻¹	For polishing smooth and glossy surfaces.
2. Med. / 350 min ⁻¹	Suitable for various tasks such as wax cleaning and interior floor polishing.
1. Low / 150 min ⁻¹	For tasks with high resistance on the pad/brush, such as anti-slip floors, and for tasks with reduced splashing of liquid.

NOISE AND VIBRATION

 Sound pressure level: **73 dB(A)**, Sound power level: **88 dB(A)**,
Vibration level: **≤2,5 m/s²**
COMPATIBILITY

 Recommended: **BL4020, BL4025, BL4040, BL4040F**
Compatible: **BL4050F, BL4080F**
RELATED PRODUCTS

**LXT 18+18 V
DHW080**
Cordless high pressure washer

197864-2
Brush for cyclone nozzle

**XGT 140 V max
VC003G**
Cordless vacuum cleaner

USER BENEFITS

- Capable of performing a wide range of tasks with a variety of attachments
- Stable operation is ensured by constant speed control and an anti-wobble structure
- Adjustable telescopic pipe can be fixed at any desired position and extends for 35,4 cm
- Removable splash guard for easier cleaning of wall edges, tile joints or grooves
- Constant speed control enables uniform polishing operations and reduces cleaning inconsistencies
- Brush/Pad replaceable without touching - when using the splash guard
- Battery cover keeps cleaning agents from adhering to the battery
- Two LED lights with afterglow function illuminate a wide area in front of the head
- Adjustable angle of the handle for optimal working posture

TECHNICAL SPECIFICATIONS

Accumulator voltage	40 V max XGT
No load speed	150 / 350 / 600 min ⁻¹
Cleaning width (brush / floor pad) Ø	190 / 200 mm
Dimensions (L×W×H)	1.081-1.435 x 204 x 361 mm
Weight*1	4,4 kg


*1 With BL4025 battery

ACCESSORIES

Brush	Bristle type	Application	Code
	Soft	For cleaning wooden floors, decks, etc.	1914T0-6
	Medium	For cleaning general interior floors.	1914T1-4
	Hard	For cleaning exterior concrete floors and removing grease stains from kitchens and similar areas.	1914T2-2
	Hard - with abrasive	For cleaning porcelain tiles and similar surfaces.	1914T3-0
Floor pad	Grit	Application	Code
	 Fine ↑ ↓ Coarse	For surface polishing of resin wax.	1914S5-9
			1914S6-7
		For cleaning of resin wax.	1914S7-5
		For removing resin wax.	1914S8-3
			1914S9-1


Pad holder - hook and loop
1914S4-1

Accessory bag
1915D1-8



AVAILABLE AS

SKR001Z without battery and charger, with LXT battery adapter

USER BENEFITS

- Achieves high-precision leveling in various sites, from residential foundations and building concreteplacements to large-scale construction sites and leveling
- Compatible with three types of batteries: XGT, LXT and CXT
- Measurement range: Diameter of 800 m (with laser receiver)
- Radio remote control RC1 with operable range of 100 m
- Digital laser receiver LDX2 with detection accuracy $\pm 0,5$ mm, center deviation display in numerical values and anti-strobe function which ignores other light sources
- Four-stage rotation speed settings 0/150/300/600 min⁻¹

TECHNICAL SPECIFICATIONS


Accumulator voltage	XGT 40 V max / LXT 18 V / CXT 12 V max
Laser type	class II , 520 nm
Automatic calibration range	$\pm 5^\circ$
Measurement range with receiver	800 m
Plumb beam	up
Scan mode	10 / 20 / 30°
Accuracy - horizontal	$\pm 0,5$ mm / 10 m
Accuracy - vertical	$\pm 0,75$ mm / 10 m
Thread mount for tripod	5/8"
IP rating (without/with battery)	IP67 / IP66
Dimensions (L×W×H)	250 x 250 x 309 mm
Weight*1	4,9 kg

*1 With BL4040 battery

PRODUCT HIGHLIGHTS




Four-directional rubber handles
The handles absorb impact from drops or tripod tip-overs while their ergonomic shape provides easy handling even with gloves.



Self leveling accuracy correction
If the self-leveling accuracy falls outside the specified range over time, it can be manually adjusted without the need for taking it to an authorized service.



5/8" mounting holes
Vertical and horizontal mounting points for attaching a tripod.



Plumb beam
By placing the device horizontally and combining the plumb beam with the horizontal line, the device can be used for various tasks such as partitioning, installing suspended ceilings, air conditioning, and piping, etc.

ACCESSORIES

Battery adapter
LE00981913 XGT
LE00981912 LXT
LE00981911 CXT

Wall mount
LE00981930

Laser receiver LDX2
LE00981928



Receiver bracket
LE00835249

Target plate - green
LE00823195

Remote control RC1
LE00981929



Tripod 400-1.100 mm
TKOLM2000F

Tripod 680-1.800 mm
TKOLM4001F

Tripod 780-2.900 mm
TKOLM5030F



COMPATIBILITY XGT

Recommended: BL4020, BL4025, BL4040, BL4040F

COMPATIBILITY LXT

Recommended: BL1815N, BL1820B, BL1830B, BL1840B, BL1850B, BL1860B

COMPATIBILITY CXT

Recommended: BL1016, BL1021B, BL1041B, BL1050B

RELATED PRODUCTS



LR20 1,5 V
SKR200Z
Rotary self-leveling laser



MAKITA d.o.o.,
Brnčičeva 17, 1231 Ljubljana-Črnuče, Slovenia
T: +386 (0) 59 083 600, E: info@makita.si


AVAILABLE AS
TW002GZ without battery and charger | **TW002GM201** with 2xBL4040 battery, DC40RA charger and Makpac 3 case

USER BENEFITS

- Suitable for professionals in construction, automotive, and heavy-duty maintenance who require high torque for demanding fastening and loosening tasks.
- Delivers 1,700 Nm of max torque and 2,200 Nm of nut-busting torque.
- Compact design with 12.7 mm (1/2") square drive for chassis maintenance and construction work with C ring socket retention.
- Electronic 4-stage impact power selection and 3 auto-stop modes for forward and reverse rotation.
- Full-speed trigger switch reduces hand and finger fatigue.
- Twin LED job lights with preglow and afterglow functions for better visibility.
- The impact wrench features variable speed, constant speed and electric brake

TECHNICAL SPECIFICATIONS

Accumulator voltage	40 V max XGT
No load speed	0 - 850/900/1.000/1.800 min ⁻¹
Impacts per minute	0 - 1.700/1.800/2.000/2.400 min ⁻¹
Square drive	1/2"
Max fastening torque	1.700 Nm
Nut busting torque	2.200 Nm
Standard bolts	M12 - M36
High strenght bolts	M10 - M27
Dimensions (L×W×H)*	213 x 94 x 297 mm
Weight*	3,9 kg


** With BL4025 battery*
PRODUCT HIGHLIGHTS

3 assistance auto stop modes

Mode	Tightening	Loosening
1	Stops immediately after impact is detected	Stops immediately after the bolt/nut gets loosened
2	Stops ~0,5 s after impact is detected	Stops ~0,2/0,3 s after the bolt/nut gets loosened
3	Stops ~1 s after impact is detected	After the last detected impact, the tool reduces the speed


Battery Cushioning Mechanism

The battery housing is separated and features an anti-vibration rubber structure to reduce terminal chattering and battery rail wear


Full speed mode

Switches between variable and full speed with a button press, reaching full speed with less trigger pull to reduce user fatigue during continuous work.


NOISE AND VIBRATION

Sound pressure level: **85 dB(A)**, Sound power level: **103 dB(A)**, Vibration level: **24,0 m/s²**


COMPATIBILITY

Recommended: **BL4040F, BL4040, BL4025, BL4020**
Compatible: **BL4050F, BL4080F**

ACCESSORIES

Hook
346949-3



Extension handle
191667-2



Set of Impact BLACK sockets 8-21 mm
E-16570



Set of Impact BLACK deep sockets 10-32 mm
E-16586


RELATED PRODUCTS


40 V max XGT
TW001G
Cordless impact wrench - 3/4"



LXT 18 V
DTW1001
Cordless impact wrench - 3/4"



LXT 18 V
DTW1002
Cordless impact wrench - 1/2"



LXT 18 V
DTW1004XV
Cordless impact wrench - 1/2"


AVAILABLE AS
TW010GZ without battery and charger | **TW010GT201** with 2x BL4050F battery, DC40RA fast charger and plastic case

USER BENEFITS

- For tightening large diameter bolts
- Extended anvil to reach deep well fasteners
- Auto-stop assist modes available in both forward / reverse rotation modes
- LED ring light provides 360° illumination to help eliminate shadows for a better view of the workpiece
- 360° toolless side handle installation with forward and back angle adjustment for fast and easy handle positioning
- Rubber damper joint between the battery and the tool protects the battery from vibrations
- Tethering ring for hanging of the tool or strap installation
- Full speed mode function reduces trigger pull to reach full speed

TECHNICAL SPECIFICATIONS

Accumulator voltage	40 V max XGT
No load speed	0-600 / 700 / 850 / 1.200 min ⁻¹
Impacts per min	0-1.200 / 1.300 / 1.500 / 1.750 min ⁻¹
Square shank	1"
Standard / high strength bolts	M27-M45 / M20-M33
Max. fastening torque	3.150 Nm
Nut-busting torque	4.000 Nm
Dimensions (L×W×H)*1	570 x 135 x 276 mm
Weight*1	12,0 kg

**1 With BL4040F battery*
PRODUCT HIGHLIGHTS


Full speed mode button
By switching to full speed mode, full speed is reached with less trigger pull, reducing fatigue in continuous operation.



Side handle 360° position and angle adjustment
Fast and easy handle positioning without the need to tools.



Auto stop assist mode in forward/reverse
Automatically stops the tool in seconds after detecting the first impact blow in forward or as soon as it stops impact blow in reverse to prevent overtightening or nut falling off.



LED ring light
Provides 360° illumination with preglow/afterglow function and light mode which turns the impact wrench into a work light.


NOISE AND VIBRATION

Sound pressure/power level: **103/111 dB(A)**,
Vibration level: **33,4 m/s²**


COMPATIBILITY

Recommended: **BL4040F, BL4050F, BL4080F**
Compatible: **BL4040**

ACCESSORIES

Socket	Size	Code	Size	Code
	1" / 27 x 60 mm	E-24511	1" / 27 x 90 mm	E-24686
	1" / 32 x 63 mm	E-24533	1" / 32 x 90 mm	E-24701
	1" / 36 x 66 mm	E-24561	1" / 36 x 90 mm	E-24739
	1" / 42 x 68 mm	E-24608	1" / 41 x 90 mm	E-22420
	1" / 46 x 72 mm	E-24620	1" / 46 x 90 mm	E-24773



O-ring 1" SQ
E-22436



Pin 1" SQ
E-22442

RELATED PRODUCTS


XGT 40 V max
TW001G
Cordless impact wrench



XGT 40 V max
TW002G
Cordless impact wrench



USER BENEFITS

- Compact, lightweight and easy to maneuver this blower is perfect for cleaning around job sites, in grooves and chemical anchor holes or for clearing pathways
- Optional vacuum function by moving the nozzle to the suction inlet and attaching the dust bag
- 3-stage air volume setting with variable speed control by trigger
- Compatible with various optional attachments
- XPT water protection

TECHNICAL SPECIFICATIONS

Accumulator voltage	40 V max XGT
Nozzle	Short / Long
Blowing force	3,1*1-3,2*2 / 3,0*1-3,1*2 N
Maximum air velocity	0-99 / 0-76 m/s
Max air volume (blowing)	0-3,6 m ³ /min
Max air volume (vacuuming)	2,0 m ³ /min
Max sealed suction (vacuuming)	5,4 kPa
Dimensions (L×W×H)*1	515 x 156 x 227 / 859 x 156 x 230 mm
Weight*1	2,0 kg

*1 With BL4025 battery / *2 With BL4040F battery

AVAILABLE AS

UB002GZ01 without battery and charger, with short and long nozzle

PRODUCT HIGHLIGHTS



Vacuum function
By moving the nozzle to the suction inlet and attaching an optional dust bag the blower can be used to vacuum fine dust.



Extremely versatile
Large range of compatible nozzles and attachments.



Continuous use
With BL4025 on a full battery charge.

Blower:
20 / 60 / 120 min
Vacuum:
19 min



Precise air control
3-stage air volume settings by dial, with variable speed control by trigger.

ACCESSORIES

Short nozzle
123245-4



Long nozzle
123246-2



Long nozzle with turned up end
191609-6



Flexible hose
191M34-3



Set of flexible hose and long nozzle
196643-5



Dust bag
123241-2



Brush nozzle
191M30-1



Wiper nozzle
191M32-7



Tapered nozzle
192236-6



NOISE AND VIBRATION

Sound pressure/power level: **84/92 dB(A)**,
Vibration level: **≤ 2,5 m/s²**

COMPATIBILITY

Recommended: **BL4020, BL4025, BL4040, BL4040F**
Compatible: **BL4050F, BL4080F**

RELATED PRODUCTS



XGT 40 V max
UB001G
Cordless blower



XGT 40 V max
VS001G
Cordless vacuum sweeper



XGT 40 V max
VC004GL
Cordless vacuum cleaner



USER BENEFITS

- Delivers strong and consistent power for trimming trees, pruning orchard trees or help building wooden structures
- Rear hand guard
- Lock-off lever accessible from both sides
- High water resistance
- Optional hook with quick attachment system allowing the tool to be hung on the belt
- Equipped with a high power BL motor

TECHNICAL SPECIFICATIONS

Accumulator voltage	40 v max XGT
Guide bar length	150 mm
Output power	0,59 kW
Saw chain pitch	0,325"
Saw chain gauge	1,1 mm
Chain speed	8,0 m/s
Oil tank capacity	55 ml
Dimensions (L×W×H)*1	485 x 95 x 257 mm
Weight*1	2,4 kg

*1 With BL4040 battery

AVAILABLE AS

UC029GZ without battery and charger | UC029GM201 with 2x BL4040 battery, DC40RA charger and Makpac 4 case

PRODUCT HIGHLIGHTS



Automatic chain lubrication
Reduces the possibility of saw chain stalling due to a lack of supply chain oil.



Easy chain adjustment
Tool-free chain adjustment for convenient operation and maintenance



Retractable guard
Covers the upper side of guide bar, and opens gradually wider as saw chain cuts deeper in branch.



Optional hook
Hook with quick attachment system allows the attachment / detachment of the tool to a carabiner or something similar with only one hand.

ACCESSORIES

Guide bar
1912F1-4



Saw chain
1912E8-3



Guide bar protection cover
413T67-3



Filing set
D-72154



Holster
1913K4-9



Hook
1914Y8-5



NOISE AND VIBRATION

Sound pressure level: **81 dB(A)**, Sound power level: **89 dB(A)**,
Vibration level: **4,6 m/s²**

COMPATIBILITY

Recommended: **BL4020, BL4025, BL4040, BL4040F, PDC1200, PDC1500**

RELATED PRODUCTS



XGT 40 V max
UC0066
Cordless chain saw



XGT 40 V max
UC0036
Cordless chain saw



XGT 40 V max
UA0046
Cordless telescopic pole saw



XGT 40 V max
UA0036
Cordless pole saw



MAKITA d.o.o.,
Brnčičeva 17, 1231 Ljubljana-Črnuče, Slovenia
T: +386 (0) 59 083 600, E: info@makita.si